

5233582-2

Fiber Optic Pigtail, singlemode, SC/PC to pigtail, 900 µm tuned, 2 m, white

Product Classification

Portfolio	NETCONNECT®
Product Type	Fiber pigtail, simplex
Regional Availability	Australia/New Zealand EMEA

Body Features

Boot Color (End A)	Red
Connector Color (End A)	Blue

Configuration Features

Number of Connectors (End A)	1
Number of Connectors (End B)	0
Exit Angle to Exit Angle	180° to 180°

Construction Materials

Jacket Color	White
Total Fibers, quantity	1

Dimensions

Assembly Length	2.00 m 6.56 ft
Cable Outer Diameter	.90 mm

General Specifications

Interface, connector A	SC
Interface, connector B	Unterminated
Interface Feature, connector A	Standard

Industry Standards

Flammability Rating	LSZH
---------------------	------

Product Type Features

Fiber Diameter	9/125 µm
Ferrule Material	Ceramic
Fiber Cable Buffering	Semi-tight buffer
Optical Mode	Singlemode

Signal Characteristics

Insertion Loss, maximum (End A)	0.30 dB
Insertion Loss, maximum (End B)	0.30 dB
Return Loss, minimum	45 dB

5233582-2

Regulatory Compliance/Certifications

Agency

RoHS 2011/65/EU

Classification

Compliant

* Footnotes

Assembly Length Assembly length includes the breakout lengths