



1375055-1

**SL110 Series Modular Jack, RJ45, category 6, T568A/T568B, unshielded, without dust cover, light almond**

## Product Classification

Portfolio	NETCONNECT®
Product Series	SL Series
Product Type	Modular jack
Regional Availability	Asia   Latin America   North America

## Body Features

110 Block Material	Polycarbonate
Inverted Jack Face	Yes

## Configuration Features

Keyed	No
Number of Positions	8
Wiring Pattern	Universal

## Contact Features

Contact Base Material	Beryllium copper
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Thickness	50.00 µin   1.27 µm

## Dimensions

Insulated Conductor Outside Diameter	0.057 in   1.45 mm
Solid Wire Range	.51 mm <sup>2</sup>   .65 mm <sup>2</sup>
Stranded Wire Range	.14 mm <sup>2</sup>   .2 mm <sup>2</sup>
Wire Range	22 AWG   24 AWG   26 AWG

## Housing Features

Housing Color	Light almond
Housing Material	Polycarbonate

## Industry Standards

UL Flammability Rating	UL 94V-0
------------------------	----------

1375055-1

## Mechanical Attachment

---

Mounting Type SL Series Faceplate

## Other

---

Comment With strain relief.

## Packaging Features

---

Packaging Method Poly Bag

Packaging Quantity 1

## Product Type Features

---

Performance Category Category 6

Shielded No

Applies To Panel

Cable Type Unshielded Twisted Pair

Connector Type Connector Assembly

Dust Cover Without

Jack Type RJ45

## Termination Features

---

Termination Method to Wire/Cable Insulation Displacement Crimp (IDC)

Termination Style SL Termination Tool

## Regulatory Compliance/Certifications

---

### Agency

RoHS 2011/65/EU

### Classification

Compliant