


1711195-1

Copper Cable, category 7, 4 pair duplex, F/FTP, LSZH, PiMF600, 23 AWG solid, 500 m, white



Product Classification

Portfolio	NETCONNECT®
Product Type	Twisted pair cable
Regional Availability	Australia/New Zealand EMEA

Standards And Qualifications

EN50575 CPR Cable EuroClass	Dca s2 d1 a1
-----------------------------	--------------------

Construction Materials

Jacket Material	Low Smoke Zero Halogen (LSZH)
Conductor Material	Bare copper
Insulation Material	Polyolefin
Shield (Tape) Material	Aluminum/Polyester

Dimensions

Cable Length	500 m 1640 ft
Cable Weight	104.00 kg/km
Diameter Over Jacket	15.000 mm 0.591 in

Electrical Specifications

ANSI/TIA Category	7
Characteristic Impedance	100 ohm
Characteristic Impedance Tolerance	±15 ohm
Nominal Velocity of Propagation (NVP)	78 %
Transmission Standards	ANSI/TIA-568-C.2 CENELEC EN 50288-6-1 ISO/IEC 11801 Class E

Environmental Specifications

Installation Temperature	0 °C to +50 °C (+32 °F to +122 °F)
Operating Temperature	-20 °C to +60 °C (-4 °F to +140 °F)

General Specifications

Cable Type	F/FTP (shielded)
Packaging Type	Reel
Pairs, quantity	8
Cable Component Type	Horizontal

1711195-1

Jacket Color	White
Brand	NETCONNECT®
Conductor Gauge, singles	23 AWG
Conductor Type, singles	Solid
Conductors, quantity	16

Mechanical Specifications

Minimum Bend Radius, multiple bends 60.00 mm | 2.36 in

Regulatory Compliance/Certifications

Agency	Classification
RoHS 2011/65/EU	Compliant
CENELEC	EN 50575 compliant, Declaration of Performance (DoP) available