



- NO 16:5

  1. INSTALLATION SHALL COMPLY WITH ALL APPLICABLE NATIONAL, STATE AND LOCAL CODES.

  2. PLEASE REFER TO PRODUCT DOCUMENTATION FOR FURTHER INFORMATION.

  3. UNLESS OTHERWISE SPECIFIED, ALL DIMENSIONS ARE IN MILLITERS (INCHES).

  4. MOUNTING BUITON IS AN ALTERNATIVE MOUNTING METHOD TO THE TROUBESS MOUNT FOR 3RD PARTY ENCLOSURE.


  BUITON IS PROVIDED WITH THE UNIT. DETAILED INSTALLATION INSTRUCTIONS CAN BE FOUND IN THE PROVIDED MANUAL.

  5. BRACKET KITS TO MOUNT TO SPECIFIC SAP PARTY ENCLOSURES ARE AVAILABLE AS OPTIONS.

  6. LENGTH OF THE CORD IS 3000HM-/-70HM

  7. DIMENSION DILERANCE: EIGHTH -/-3HM, WIDTH +/-IMM, DEPTH +/-0.5MM

  8. REFER TO THE TABLE FOR DETAIL CORD LENGTH DEFINITION



## A brand of 🖾 legrand

Eva Lin Aug. 29, 2017 Aug. 29, 2017 Design Engineer: Siang\_H Aug. 29, 2017 Tom\_H Approver:



PROJECTION THIRD ANGLE

DO NOT SCALE DRAWING SHEET 1 OF 1

THIS DRAWING AND SPECIFICATIONS HEREIN ARE THE PROPERTY OF RARITAN, Inc. AND SHALL NOT BE COPIED, REPRODUCED OR USED, IN WHOLE OR IN PART, AS THE BASIS FOR THE MANUFACTURE OR SALE OF ITEMS WITHOUT WRITTEN PERMISSION FROM RARITAN, Inc. THIS DRAWING IS BASED UPON LATEST AVAILABLE INFORMATION AND IS SUBJECT TO CHANGE WITHOUT NOTICE.

TITLE: ¡PDU Zero U

Single Phase, 32A/200-240V Plug Type: IEC60309 32A Outlet Type: C13 (12), C19 (4)

MPX3-5397 M5 & MPX3-4397 M5

PX3-5397 & PX3-4397 PX3-5397-M5 & PX3-4397-M5

REV. **2A**