

Indoor/Outdoor Lockable Wall Box up to 24 Fibres

Description

This Lockable IP65 distribution box is supplied unloaded as standard and offers the ability to terminate 24 fibres housed in a strong robust ABS enclosure for indoor and outdoor applications. An internal detachable tray provides a neat and tidy solution for housing 24 SC simplex connections and splices. The box has 24 patchcord exit points and up to 2 cable entry points which maintain the IP65 rating. Integrated cable tie points are included to secure incoming cables. A locking feature for the door adds extra security when positioned in un-secure areas.

Features/Benefits

- ▶ IP 65 Rating for external use
- ▶ Lockable door for added security
- ▶ Integrated cable tie points for securing incoming cable
- ▶ Up to 24 splice & SC connection points
- ▶ Removable splice tray for easy installation
- ▶ Accepts loose tube, distribution and pre-terminated cables
- ▶ Integrated bend radius protection
- ▶ Sealing glands for up to 24 exiting cables + 2 incoming cable
- ▶ Removable door for ease of installation
- ▶ Supplied with 24 heatshrink splice protectors
- ▶ Supplied with transit tubing
- ▶ Supplied with wall fixings and tie wraps
- ▶ ROHS, REACH & SvHC compliant



Technical Specification

Applications

- ▶ Data centres, premise installations, telecommunication networks
- ▶ Ethernet, Fibre Channel, ATM, LAN, MAN and WAN
- ▶ Data communication and telecommunication networks
- ▶ Indoor/outdoor applications

Element	Characteristic
Height (mm)	340
Width (mm)	270
Depth (mm)	110
Net weight (kg)	1.8
Suitable for adaptor type	SC Simplex
Number of ports	24
Cable entry	2
Material	ABS
Colour	Grey RAL 7035
Operating temperature (°C)	-40 to +60
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754, EN297-1
Compliant to	RoHS, Reach/SVHC