

Indoor/Outdoor Lockable Wall Box up to 12 Fibres

Description

This Lockable IP65 distribution box is supplied unloaded as standard and offers the ability to terminate 12 fibres housed in a strong robust ABS enclosure for indoor and outdoor applications. An internal detachable tray provides a neat and tidy solution for housing 12 SC simplex connections and splices. The box has 12 patchcord exit points and up to 2 cable entry points which maintain the IP65 rating. Integrated cable tie points are included to secure incoming cables. A locking feature for the door adds extra security when positioned in un-secure areas.



Features/Benefits

- ▶ IP 65 Rating for external use
- ▶ Lockable door for added security
- ▶ Integrated cable tie points for securing incoming cable
- ▶ Up to 12 splice & SC connection points
- ▶ Removable splice tray for easy installation
- ▶ Accepts loose tube, distribution and pre-terminated cables
- ▶ Integrated bend radius protection
- ▶ Sealing glands for up to 12 exiting cables + 2 incoming cable
- ▶ Removable door for ease of installation
- ▶ Supplied with 12 heatshrink splice protectors
- ▶ Supplied with transit tubing
- ▶ Supplied with wall fixings and tie wraps
- ▶ ROHS, REACH & SvHC compliant

Applications

- ▶ Data centres, premise installations, telecommunication networks
- ▶ Ethernet, Fibre Channel, ATM, LAN, MAN and WAN
- ▶ Data communication and telecommunication networks
- ▶ Indoor/outdoor applications

Technical Specification

ELEMENT	CHARACTERISTIC
Height (mm)	235
Width (mm)	205
Depth (mm)	60
Net weight (kg)	0.9
Suitable for adaptor type	SC Simplex
Number of ports	12
Cable entry	2
Material	ABS
Colour	Grey RAL 7035
Operating temperature (°C)	-40 to +60
Designed in accordance with	TIA/EIA 568.C, ISO/IEC 11801, EN50173, IEC60304, IEC61754, EN297-1
Compliant to	RoHS, Reach/SVHC